



شركة سمارت للدهانات SMART PAINT COMPANY

EGGSHELL

Product Description:

A high quality water-based paint based on acrylic polymers and high quality coloring materials. After application, it gives a smooth, regular, bright white surface that resembles an egg shell. It also gives long-term protection to the internal surfaces, it is characterized by high resistance to different atmospheres and with a high brushing rate and coverage.

The use:

It is used for interior applications of concrete, cement and gypsum coatings.

Properties:

- Unique coverage
- Super smoothness
- Easy to apply without splashing
- Excellent adhesion strength
- Suitable for all building materials surfaces
- Good alkali resistance
- Very good wash ability

Certification:

Conforming to Jordanian standard specification 31/2021





شركة سمارت للدهانات SMART PAINT COMPANY



Physical properties:

| | | |
|-------------------------|--|------------|
| general look | A shiny quarter | |
| Color | White according to the colors supported in the catalog | |
| Specific weight | 0.05 ± 1.30 | ASTM D1475 |
| Solid size | 40 ± 2 % | ASTM D2697 |
| Dry layer thickening | 40-50 Micron | |
| Theoretical spread rate | 8-10 m ² /liter | |



Drying time:

| | |
|----------------------|---------------|
| Surface dry 24 hours | 30-60 minutes |
| Hard dry | 2- 4 hours |
| Re-application | 6 hours |
| Complete dry | 24 hours |

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and bumps.

Instructions for use:

The paint should be stirred well before use.

Sufficient amount of water may be added to obtain the appropriate viscosity for the application.

Do not paint over wet surfaces until after they are completely dry.

Not to paint the next layer unless the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and dehydration





شركة سمارت للدهانات SMART PAINT COMPANY

Application tools: roller, brush and spray.

Diluent: water.

Dilution percentage: 20-30%.

Storage conditions:

As it is in the original Golden Bulletin

Shelf life: one year from the date of production.

